HOSES AND TUBING

LOW PRESSURE

TEXTILE BRAID



OTHER HOSES



RUBBER MULTI-PURPOSE





TEXTILE BRAID

SFR6 - R6 PUSHLOCK HOSE

VERY LOW PRESSURE AND LOW IMPULSE HYDRAULIC LINES 20 TO 35 BAR.

For use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural, Stationary equipment and hydraulic systems.

PROPERTIES

| APPLICATION | Very low pressure and low impulse hydraulic lines 20 to 35 bar. For use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural, Stationary equipment and hydraulic systems. |
|--|--|
| APPLICABLE STANDARD Standard: SAE J517 – 100 R6 / EN 854 | |
| REINFORCEMENT | Single fibre braid |
| TEMPERATURE RANGE | Continuous: -40°C to +120°C |



| CODE | DESCRIPTION | HOSE BORE | | HOSE O.D. *It is normal for this to vary slightly due to manufacturing processes | WORKING | PRESSURE | MINIMUM BEND RADIUS |
|---------|------------------------|------------|------------|--|---------|----------|---------------------------|
| | | (I.D) Inch | (I.D) (mm) | (mm) | (PSI) | (BAR) | |
| SFR6-03 | 3/16" R6 PUSHLOCK HOSE | 3/16" | 4.8 | 11.9 | 508 | 35 | 50 |
| SFR6-04 | 1/4" R6 PUSHLOCK HOSE | 1/4" | 6.4 | 13.5 | 435 | 30 | 65 |
| SFR6-05 | 5/16" R6 PUSHLOCK HOSE | 5/16" | 8 | 15.1 | 435 | 30 | 80 |
| SFR6-06 | 3/8" R6 PUSHLOCK HOSE | 3/8" | 9.5 | 16.7 | 435 | 30 | 80 |
| SFR6-08 | 1/2" R6 PUSHLOCK HOSE | 1/2" | 12.7 | 20.6 | 435 | 30 | 100 |
| SFR6-10 | 5/8" R6 PUSHLOCK HOSE | 5/8" | 16 | 23.8 | 363 | 25 | 125 |
| SFR6-12 | 3/4" R6 PUSHLOCK HOSE | 3/4" | 19 | 27.8 | 305 | 21 | 150 |

NZ: 0800 20 20 20 | AU: 1800 40 30 40 | +64 9 579 2103

FUEL HOSE

RFU - FUEL LINE

DESIGNED FOR USE IN VEHICLE FUEL SYSTEMS FOR THE TRANSFER OF PETROLEUM PRODUCT UNDER LOW PRESSURE.

PROPERTIES

| APPLICATION STANDARD | ARD SAE30R7 | |
|--|---------------------------------|--|
| TUBE Black smooth Nitrile rubber, 30% aromatic content. | | |
| REINFORCEMENT | RCEMENT Braided synthetic cord. | |
| COVER Black Colour, synthetic fuel and oil resistance rubber | | |
| TEMPERATURE RANGE | -35°C to +100°C | |



| | | | 0 | WORKING PRESSURE | | <u>lududur</u> | |
|----------|----------------------|-----------|--|------------------|---|--|--|
| CODE | DESCRIPTION | HOSE BORE | HOSE O.D. *It is normal for this to vary slightly due to manufacturing processes | | | FULL COIL SIZE * (M) *Coil size indiciates the usual coil full coil size, but does not guarantee full coils will always be available | |
| | | (mm) | (mm) | (PSI) (BAR) | | (mm) | |
| RH-RFU08 | 8MM FUEL LINE (20m) | 8 | 14 | 72.5 5 | | 20 | |
| RH-RFU10 | 10MM FUEL LINE (20m) | 10 | 16 | 72.5 5 | | 20 | |
| RH-RFU13 | 13MM FUEL LINE (20m) | 13 | 20 | 72.5 | 5 | 20 | |

MULTI PURPOSE

RMPBS - SILFLO BLACK MULTI-PURPOSE HOSE - AIR/OIL/WATER/PETROL



COST EFFECTIVE MULTI-PURPOSE RUBBER HOSE SUITABLE FOR AIR, OIL, WATER (NON POTABLE), PETROL, DIESEL, ETC. SILFLO QUALITY FOR PEACE OF MIND.

PROPERTIES

| COMMON APPLICATION Multi-purpose hose suitable for conveying air, water, oil, petroleum and various chemicals. | | | | |
|--|---|--|--|--|
| SAFETY FACTOR 3:1 Burst pressure is three times that of working pressure. | | | | |
| EXTRUDED CONSTRUCTION TUBE: | Black smooth Nitrile rubber, resistant to 55% aromatic content. | | | |
| REINFORCEMENT Braided synthetic cord. | | | | |
| COVER Rubber, wrapped construction, abrasion & weather resistant. | | | | |
| TEMPERATURE RANGE | -25 °C to 100 °C | | | |



| CODE | DESCRIPTION | HOSE BORE | | WORKING PRESSURE | | FULL COIL SIZE * (M) *Coil size indiciates the usual coil full coil size, but does not guarantee full coils will always be available | |
|---------|---|------------|------------|------------------|-------|--|--|
| | | (I.D) Inch | (I.D) (mm) | (PSI) | (BAR) | | |
| RMP10BS | 10MM SILflo BLK HOSE-AIR/OIL/WATER (100m) | 3/8 | 10 | 400 | 28 | 100 | |
| RMP13BS | 13MM SILflo BLK HOSE-AIR/OIL/WATER (50m) | 1/2 | 13 | 400 | 28 | 50 | |
| RMP16BS | 16MM SILflo BLK HOSE-AIR/OIL/WATER (100m) | 5/8 | 16 | 400 | 28 | 50 | |
| RMP19BS | 19MM SILflo BLK HOSE-AIR/OIL/WATER (50m) | 3/4 | 19 | 300 | 21 | 50 | |
| RMP25BS | 25MM SILflo BLK HOSE-AIR/OIL/WATER (50m) | 1 | 25 | 300 | 21 | 50 | |

NZ: 0800 20 20 20 | AU: 1800 40 30 40 | +64 9 579 2103

MULTI PURPOSE

RMP - RED MULTI-PURPOSE HOSE -AIR/OIL/WATER/PETROL

PREMIUM MULTI-PURPOSE RUBBER HOSE SUITABLE FOR AIR, OIL, WATER (NON POTABLE), PETROL, DIESEL, ETC. EXTREMELY VERSATILE, TOP SELLER.

PROPERTIES

| This high quality multi-purpose hose is suitable for conveying air, water, oil, petroleum and various chemicals. Note: Suitable for transfer of ULP at low pressure. No static wire. | | | |
|--|--|--|--|
| SAFETY FACTOR 3:1 Burst pressure is three times that of working pressure. | | | |
| EXTRUDED CONSTRUCTION TUBE: | Elack emonth Nitrile rubber registant to 55% aromatic content. Electronically non-conductive. (Δicoa annroyed) | | |
| REINFORCEMENT Braided synthetic cord. | | | |
| COVER Red smooth extruded rubber, abrasion & weather resistant. (Larger sizes are wrapped construction) | | | |
| TEMPERATURE RANGE | -25 °C to 100 °C | | |





| CODE | DESCRIPTION | HOSE BORE | | HOSE O.D. "It is normal for this to vary slightly due to manufacturing processes | WORKING PRESSURE | | FULL COIL SIZE * (M) *Coil size indiciates the usual coil full coil size, but does not guarantee full coils will always be available | |
|-------|---|------------|------------|--|---------------------|-------|---|--|
| | | (I.D) Inch | (I.D) (mm) | (mm) | (PSI) | (BAR) | | |
| RMP06 | 6MM RED MULTI-PURPOSE HOSE-AIR/OIL/WATER | 1/4 | 6 | 13 | 290 | 19.99 | 20, 100 | |
| RMP08 | 8MM RED MULTI-PURPOSE HOSE-AIR/OIL/WATER | 5/16 | 8 | 15 | 290 | 19.99 | 20, 100 | |
| RMP10 | 10MM RED MULTI-PURPOSE HOSE-AIR/OIL/WATER | 3/8 | 10 | 17 | 290 | 19.99 | 20, 100 | |
| RMP13 | 13MM RED MULTI-PURPOSE HOSE-AIR/OIL/WATER | 1/2 | 13 | 21 | 290 | 19.99 | 20, 100 | |
| RMP16 | 16MM RED MULTI-PURPOSE HOSE-AIR/OIL/WATER | 5/8 | 16 | 26 | 290 | 19.99 | 20, 100 | |
| RMP19 | 19MM RED MULTI-PURPOSE HOSE-AIR/OIL/WATER | 3/4 | 19 | 29 | 290 | 19.99 | 20, 100 | |
| RMP25 | 25MM RED MULTI-PURPOSE HOSE-AIR/OIL/WATER | 1 | 25 | 36 | 290 | 19.99 | 20, 100 | |
| RMP32 | 32MM RED MULTI-PURPOSE HOSE-AIR/OIL/WATER | 1 1/4 | 32 | 44 | 203 | 14.00 | 40 | |
| RMP38 | 38MM RED MULTI-PURPOSE HOSE-AIR/OIL/WATER | 11/2 | 38 | 53 | 203 | 14.00 | 40 | |
| RMP51 | 51MM RED MULTI-PURPOSE HOSE-AIR/OIL/WATER | 2 | 51 | 63 | 145 | 10.00 | 20 | |

Access and order from our full range of products on the go



www.boahub.com